

ROLL-UP SHUTTER DOORS

	DOOR OPENING WIDTH								
	24"	30"	36"	42"	48"	54"	60"	66"	72"
18"	\$540.37	\$573.94	\$607.54	\$641.13	\$674.71	\$708.30	\$741.84	\$775.45	\$809.01
24"	593.83	630.77	667.68	704.61	741.54	778.46	815.38	852.32	889.24
30"	647.30	687.57	727.84	768.08	808.35	848.62	888.89	929.16	969.43
36"	700.77	744.38	787.98	831.59	875.20	918.80	962.41	1,006.02	1,049.65
42"	754.22	801.18	848.13	895.07	942.01	988.96	1,035.95	1,082.89	1,129.84
48"	807.68	857.99	908.27	958.58	1,008.86	1,059.17	1,109.45	1,159.74	1,210.03
54"	861.15	914.79	968.44	1,022.06	1,075.69	1,129.33	1,182.96	1,236.62	1,290.24
60"	914.61	971.62	1,028.57	1,085.56	1,142.53	1,199.49	1,256.48	1,313.45	1,370.43
66"	968.08	1,028.42	1,088.72	1,149.04	1,209.38	1,269.67	1,330.01	1,390.31	1,450.64
72"	1,021.56	1,085.23	1,148.88	1,212.54	1,276.19	1,339.86	1,403.53	1,467.16	1,530.83
78"	1,075.02	1,142.03	1,209.65	1,276.04	1,343.04	1,410.04	1,477.22	1,544.03	1,611.02
84"	1,134.13	1,204.84	1,276.19	1,346.22	1,416.90	1,487.61	1,558.44	1,628.94	1,699.64
90"	1,196.51	1,271.11	1,346.39	1,420.25	1,494.81	1,569.44	1,644.15	1,718.55	1,793.11

- Each door is manufactured of bright brushed anodized aluminum.
- Doors are complete with side seals, two-point slam lock and dual header seal.
- Track assembly of aluminum or galvanized steel.
- Stainless steel lock included.

Non-brush anodized panels – deduct 5% from basic door price

Options:

Stainless steel recessed Lift handle	\$12.55
Panel joint seal	\$2.41
Aluminum track	\$9.53
Non-locking bar lock (up to 50" o.w.)	n/c
(Over 50" o.w.)	\$28.58 NET
Locking bar lock (up to 50" o.w.)	\$22.86 NET
(Over 50" o.w.)	\$51.44 NET

For larger sizes and special applications, contact the nearest TODCO factory.

LUBRICATION



- Lubricate the counterbalance bearings, spring, roller hinges and lock liberally with TODCO FG Lube.
- DO NOT USE GREASE.
- Frequency of door maintenance will vary with climate conditions and door cleaning procedures. Doors which are steam cleaned on the interior face will need lubricating more often than those not cleaned by this method. Doors on equipment which will run in areas where road salts are used will require lock lubrication at closer intervals.
- Lubrication should increase with cleaning frequency.

PLEASE NOTE:

- All prices shown or quoted are for one assembled door complete with all door hardware.
- F.O.B. shipping factory.
- Effective Date: July 1, 2014. Supersedes all previous Price Lists.
- Prices subject to change without notice. Surcharge may apply.
- For complete information or recommendations on specific requirements, contact your nearest TODCO plant or any of our representatives.
- High pressure wash or harsh cleaning solutions can damage door finish.