



# ARCTIC FLEX<sup>®</sup>

## SINGLE PANEL CONSTRUCTION

Eliminates panel joints, where typically, ambient temp (heat gain), dust, and moisture can enter the cargo bay.

## SMOOTH SUBSTRATE

Free of rivets (excluding exterior hardware) for easier application of fleet advertising.

## 57% LIGHTER WEIGHT

Than competitor's 2 1/8" insulated door.

**43% lighter** than the competitor's 1 1/2" insulated door

Reduced weight increases spring life and reduces fuel and maintenance costs

## EXCELLENT THERMAL EFFICIENCY:



**20% more** thermally efficient than the competitor's 1 1/2" insulated doors, similar in thermal efficiency to the competitor's 2 1/8" insulated door.

## LOWER MAINTENANCE COST

**SuperRoller™** is included, which last 5-10 times longer than standard rollers. Also includes stainless steel and aluminum hardware for rust prevention.



## IMPROVED SAFETY

Single panel design eliminates pinch points.

## MOLD RESISTANT MATERIALS

## EASILY CLEANED & REPAIRED



**5 YEAR**  
LIMITED WARRANTY

**CONTACT YOUR REP TODAY**  
800-999-3392 • [TODCO.COM](http://TODCO.COM)

**MILES THAT MATTER**